
Starlike® Wall Care

Technical specifications



Gel detergent for the removal of epoxy wall stains from all types of tiles, mosaics and natural stones

Product description

Starlike® Wall Care is a concentrated liquid detergent in Gel form, with an alkaline pH ideal for cleaning all types of ceramic and porcelain tiles, including delicate surfaces such as honed ceramics, vitreous or ceramic mosaics, and any type of natural stone, including polished. Starlike® Wall Care, characterised by high viscosity, is particularly suitable for cleaning ceramic wall coverings.

Performance

Versatile and usable on all surfaces.
Water-based product.
Non-aggressive solution, which can also be used on polished marble and honed or polished stoneware without the risk of corrosion or tarnishing.
Exempt from hazard classification for transport.
Excellent degreasing and wax removal power.

Uses

Used undiluted, the detergent is particularly effective for the removal of aged residues and stains from epoxy grouts such as Starlike® Pro, Starlike® Crystal or Starlike® Easy, as well as for the removal of stains on polished porcelain stoneware, stained by previous grouting with dark-coloured cementitious sealants.
De-greasing alkaline detergent: effective in removing greasy residue, organic dirt deposits accumulated over time and wax from all natural or artificial surfaces. In this case, dilute the product at a rate of 30% in water.

Periodic deep cleaning detergent: effective on all types of surfaces characterised by intense dirt, which cannot be removed using commonly sold detergents.

Product specifications

Appearance	Starlike® Wall Care - Transparent Gel liquid
Colour	Colourless
Odour	Peach
Customs code	3402909000
Responsible packaging	0.75 litre recycled plastic bottles with spray nozzle
Shelf life	24 months in original packaging away from sources of heat and direct sunlight. Protect against frost.

Specifications for application

Treatment time	10 - 15 minutes
Flammable	No
pH	11,5 - 12,5
Specific gravity	1.01 kg/l
Application	Starlike® sponge or white felt
Application temperatures	From +5°C to +35°C
Consumption	10 - 15 m ² /l

Application

Shake well before use.

For the removal of epoxy grout halos or residue, the detergent must be applied once the grouting has sufficiently set (normally after 24 hours at a temperature of +20/+25°C).

For fresh residue the product requires less time to work, while for more consolidated residue, the product will need to be left in contact for longer.

Apply the pure, undiluted product, by spraying it directly onto the affected surface and spreading it evenly with a suitable white Starlike® pad or felt. Leave it on for about 10-15 minutes.

It is recommended to mechanically rub the product when applied to facilitate its removal.

Collect the cleaning solution with a damp sponge.

Finally, rinse well with clean water and dry with a clean rag or cloth.

Do not wait for the rinse water to evaporate as this may cause stains to reappear on the surface.

If epoxy grout residue can still be seen after rinsing, repeat the application following the same procedure.

Warnings

Apply the product at temperatures between +5°C and +35°C

Wear protective clothing during handling. Follow the instructions shown on the label and safety sheet

Before use, protect doors, windows, rubber gaskets, furniture, taps and fittings, metal or PVC profiles and all surfaces that may be damaged by direct contact with the detergents

Change the rinse water frequently

In the case of accidental leaks, soak up the product using an absorbent material (paper, sawdust, vermiculite, etc.) and dispose of it in a suitable container

Do not use the product for applications not indicated in this technical data sheet

For further information, contact the Litokol Technical Help Service at +39-0522-622811 or via customer care@litokol.com

Information regarding safety

For the safe use of our products, refer to the latest version of the Safety Data Sheet, available on the website www.litokol.com
PRODUCT FOR PROFESSIONAL USE

Legal notes

The information and provisions contained in this technical data sheet reflect our best experience.

Given the impossibility of directly intervening on the conditions of the work site and execution of the works, they represent indications of a general nature, which are in no way binding for our Company.

It is therefore recommended to perform a spot test in order to check the suitability of the product for the intended use. In any case, those who intend to use the product must establish whether or not it is suitable for the intended use, and in any case assume all liability for any consequences resulting from such use.

Always refer to the latest updated version of the technical data sheet, available on the website www.litokol.com

Data sheet **n. 410/b**

Revision **n. 0**

Date: **05 25**

Litokol

Litokol Lab Spa Via G. Falcone 13/1 42048 Rubiera RE Italy
Tel. +39 0522 622811 info@litokol.com www.litokol.com